

THE GLOBAL BENCHMARK
FOR QUALITY, SAFETY,
AND DESIGN.

SUPERPLASMA AQ CE



STANDARD

EN 397 | -30°C / LD / MM



EN 12492

for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral
impact, 4.2.1.4 rear impact
4.2.2 | Penetration



MATERIAL

EXTERNAL SHELL:
HD Polypropylene



INTERNAL SHELL:

Neopor® Cycled® by BASF | EPS
obtained from chemical recycling of
plastic waste.

HEADBAND:
Soft PA Nylon



TEMPERATURE OF USE

-30°C / +50°C



WEIGHT

390 g



SIZE

Universal-adjustable from 51 to 63 cm



WHE00104

○ 201	● 205	● 208
● 202	● 206	● 210
● 203	● 207	● 214
● 204		



CATEGORY

II

TECHNOLOGIES

- **QUICK FIT SYSTEM** Size adjustment system for maximum stability.
- **2DRY LINER** Moisture-wicking fabric technology for all-day comfort.
- **VENTILATION CHANNELS** 10 air intakes that enhance breathability and comfort.
- **ANTI-INTRUSION MESH** Prevents debris from entering ventilation channels.
- **RING TO HOOK** Chinstrap loop that securely attaches helmet to a harness.
- **EARMUFF ADAPTER ATTACHMENT POINTS** For adapters to secure earmuffs.
- **VISOR ATTACHMENT POINTS** For securing KASK eye protection accessories.
- **INTEGRATED LAMP CLIPS** 4 built-in, nylon lamp attachment points.

3

YEARS
GUARANTEE

10

YEARS
LIFE SPAN



SCAN FOR
COMPLETE
COLLECTION