

X 800

ballistic goggle

Compatible with all types of helmets, the X800 goggle is fitted with an easy-to-change panoramic lens. It has a **unique ventilation system** guaranteeing excellent fogging resistance.

PANORAMIC FIELD OF VISION

BALLISTIC LENS

ANTI-FOG COATING

EASY REPLACEMENT LENS SYSTEM



HIGH COMFORT BI-MATERIAL FRAME

ULTRA-VENTILATED FRAME



Spare lens :



FAX8I



FAX8J



FAX8F







Supplied with microfibre pouch around the strap and individual rigid carry case.

X 800

ballistic goggle

bolle
TACTICAL

markings / norms

| Model | Reference | Version | Lens markings | Frame marking | V50 Ballistic Resistance STANAG 2920 | ANSI/MIL | Coatings |
|---------------------------|-----------|--|---------------------|----------------|--------------------------------------|----------|--------------|
| X800 Goggles | X800I |  Clear | 2C-1.2 ☞ 1 BT N C € | ☞ EN166 BT C € | 716 km/h - 199 m/s | - | Anti-fog (N) |
| X800 Spare lens | FAX8I |  Clear | 2C-1.2 ☞ 1 BT N C € | - | 716 km/h - 199 m/s | - | Anti-fog (N) |
| | FAX8J |  Yellow | 2C-1.2 ☞ 1 BT N C € | - | 677 km/h - 188 m/s | - | Anti-fog (N) |
| | FAX8F |  Smoke | 5-2,5 ☞ 1 BT N C € | - | 698 km/h - 191 m/s | - | Anti-fog (N) |

CHARACTERISTICS

LENS: Ballistic PC lens - 3 mm - Curve 5
Anti-fog coating
Easy replacement lens system
FRAME: Ultra-comfortable, ultra-ventilated
bi-material frames (Nylon + TPE)
Available in black

CHARACTERISTICS

STRAP:
Wide Adjustable 35 mm strap
Helmet wearers compatible
WEIGHT: 106 g

**HIGH
RESISTANCE**

packaging and ean13 code :

| Model | Reference | Unit | Inner box | Units | Outer box | Units |
|-------------|-----------|---------------|---------------|-------|---------------|-------|
| X800 | X800I | 3660740002749 | X | X | 3660740202743 | x 60 |
| | FAX8I | 3660740001575 | 3660740101572 | x 30 | 3660740201579 | x 300 |
| | FAX8J | 3660740001582 | 3660740101589 | x 30 | 3660740201586 | x 300 |
| | FAX8F | 3660740001568 | 3660740101565 | x 30 | 3660740201562 | x 300 |

Notified laboratories for certification:



06/03/2015