




H: 178 mm D: 130 mm W: 166 mm



H: 108 mm D: 52 mm W: 68 mm

Weight

Mask + Filters: 550 g
Filters: 200 g

Shelf Life

5 years (mask & filters) See storage conditions on Instructions for Use. Filters are re-usable and changeable.

Standards

Facemask EN 136:1998 Class 1
EN166:2001 Class 1 & K (anti-scratch)
Cartridge filter EN 14387:2004+A1:2008 A2P3 R D

Efficiency

P3 >99,95% for 0,3 μ particulate
At 5000 ppm:
> 35 minutes Cyclohexane (C₆H₁₂)



Patent Pending

1. Particulate pleated filter (total length 645 mm)
2. Activated carbon treated for gas adsorption
3. Designed to help airflow diffusion and full usage of the activated carbon
4. Inhalation valve

Applications

Welding and Grinding: Metal Fumes and Dust in confined spaces (gas welding)

Constructions: Paint, Moulds

Manufacturing: Solvents, various Organic Gases



Material

- Inner mask body in Medical Grade TPE
- Visor in polycarbonate overmolded with silicone frame
- Headband in silicone
- Covers in PE
- Valve body in nylon with silicone diaphragms
- Gas Filters: Activated carbon sealed into a ABS Shell
- Particulate filters: Mechanical type multi-layer HESPA Synthetic media with TPE flexible overmolded / encapsulated. Particulate filters are integrated with the carbon element

Part #	Description
FFM221L	Elipse® Full Face A2P3 Respirator Package also includes: ■ Replaceable filters
FIL253L	Elipse® A2P3 Replacement Cartridges Pair
SPM1001	Elipse® Full Face Carry Case
SPM1002	Elipse® Full Face Face Face Fit Test
SPM1003	1 pc Tearoff Kit

