

WV100036



Polycarbonate visor with scratch-resistant coating and anti-fog treatment. The rubber profile on the upper edge protects in case of dripping and the cut proof edge ensures maximum comfort. The ergonomic and panoramic shape is compatible for overlapping corrective glasses. Screw set for mounting is included with visor.

Compatible with KASK Superplasma helmet series.

## MOUNTING PARTS



## TECHNICAL DETAILS

 <p><b>STANDARD</b> EN ISO 16321 EN 14458 <b>CE</b>  ANSI Z87.1</p>	 <p><b>CATEGORY</b> II</p>  <p><b>ENHANCED OPTICAL PERFORMANCE</b> 1</p>	 <p><b>MATERIAL</b> Polycarbonate</p>  <p><b>WEIGHT</b> 80 g</p>  <p><b>LENGTH</b> 110 mm</p>
---	--	--

## TECHNOLOGIES

 <p><b>ANTI-FOG</b> Equipped with an anti-fog treatment to increase wearer visibility when active and in a variety of conditions.</p>	 <p><b>COMPATIBLE WITH GLASSES</b> Designed for use over corrective glasses.</p>
 <p><b>CUT PROOF EDGE</b> Eye shield edge detail designed with a cut proof edge for enhanced wearer safety.</p>	 <p><b>EXTREME TEMP IMPACT RESISTANCE</b> Able to withstand impacts at extreme temperatures for use in a variety of environments.</p>
 <p><b>DRIP PROOF UPPER CONTOUR</b> Rubber edge protects eyes from liquid and debris from entering the visor.</p>	 <p><b>ABRASION AND SCRATCH RESISTANCE</b> Lens treatment designed with protection from abrasion and scratches or increased durability and viewing clarity.</p>
 <p><b>PANORAMIC LENS</b> Developed to maximize visibility with minimal viewing distortion.</p>	

## CE MARKINGS

CODE	COLOR	MARKING
WV100036-500	CLEAR	CE   EN14458:2018   <b>KASK</b>   V2 PLUS   MM/YY   =   ⊙   BT   2C-1,2   -30°C+50°C   □ <b>KASK</b>   UL1,2   DT   1   -5°C+55°C   K   N   CH   7   16321   <b>KASK</b>   DT   1-M   -5°C+55°C
WV100036-510	SMOKE	CE   EN14458:2018   <b>KASK</b>   V2 PLUS   MM/YY   =   ⊙   BT   5-1,4   -30°C+50°C   □ <b>KASK</b>   GL1   DT   1   -5°C+55°C   K   N   CH   7   16321   <b>KASK</b>   DT   1-M   -5°C+55°C
WV100036-520	SILVER MIRROR	CE   EN14458:2018   <b>KASK</b>   V2 PLUS   MM/YY   =   ⊙   BT   5-2,5   -30°C+50°C   □ <b>KASK</b>   G2   DT   1   -5°C+55°C   K   N   CH   7   16321   <b>KASK</b>   DT   1-M   -5°C+55°C

## ANSI MARKINGS

CODE	COLOR	MARKING
WV100036-500	CLEAR	ANSI Z87   +   U6   X   D3
WV100036-510	SMOKE	ANSI Z87   +   U6   L1.5   X   D3
WV100036-520	SILVER MIRROR	ANSI Z87   +   U6   L2.5   X   D3

## ADDITIONAL INFORMATION

**GUARANTEE**  
3 years starting from the date of purchase.

**LIFE SPAN**  
10 years starting from the date of manufacture. Life span depends on various factors that can cause deterioration such as sudden temperature changes, the amount of exposure to direct sunlight and the intensity of use. Altered vision and scratches are elements that signal the need to check for deterioration of the visor.

**CLEANING**  
Clean only with water and mild soap. Allow to air dry. Do not use chemical detergents, solvents, petrol powders as they are too aggressive and could lower the structural resistance of the visor.

**3**  
YEARS  
GUARANTEE

**10**  
YEARS  
LIFE SPAN

SCAN FOR COMPLETE COLLECTION

