

WVI00040



Fire-resistant, scratch-resistant, and anti-fog polycarbonate full face protection. Requires KASK Easy Click Adapters FR. Can be worn with corrective glasses.

Compatible with KASK Zenith X, Primero and Quantum helmet series.

The ZEN FF PLUS VISOR mounted on the QUANTUM helmet, via the EASY CLICK ADAPTERS FR, makes the helmet usable for use in wildland firefighting (EN16471) and technical rescue activities (EN16473) where there is potential exposure to flames.

MOUNTING PARTS



TECHNICAL DETAILS

STANDARD
EN ISO 16321
EN 14458
CE 2754

CATEGORY
III

ENHANCED OPTICAL PERFORMANCE
1

MATERIAL
Polycarbonate

WEIGHT
145 g

ANSI Z87.1

TECHNOLOGIES

PANORAMIC LENS
Developed to maximize visibility with minimal viewing distortion.

ANTI-FOG
Equipped with an anti-fog treatment to increase wearer visibility when active and in a variety of conditions.

ABRASION AND SCRATCH RESISTANCE
Lens treatment designed with protection from abrasion and scratches or increased durability and viewing clarity.

COMPATIBLE WITH GLASSES
Designed for use over corrective glasses.

DRIP PROOF UPPER CONTOUR
Rubber edge protects eyes from liquid and debris from entering the visor.

EASY CLICK ADAPTERS
Adapters designed to be easily attached and removed to KASK eye and face protection accessories.

CE MARKINGS

CODE	COLOR	MARKING
WVI00040-500	CLEAR	CE 2754 EN14458:2018 KASK ZEN FF PLUS MM/YY +R1 ⊕ BT E1/E3 2C-1,2 -30°C +50°C ☐ KASK UL1,2 ET 1 -5°C +55°C K N CH 9 16321 KASK ET 1-M -5°C +55°C 3 CH 9
WVI00040-510	SMOKE	CE 2754 EN14458:2018 KASK ZEN FF PLUS MM/YY +R1 ⊕ BT E1/E3 5-1,4 -30°C +50°C ☐ KASK GL2 ET 1 -5°C +55°C K N CH 9 16321 KASK ET 1-M -5°C +55°C 3 CH 9
WVI00040-520	SILVER MIRROR	CE 2754 EN14458:2018 KASK ZEN FF PLUS MM/YY +R1 ⊕ BT E1/E3 5-2,5 -30°C +50°C ☐ KASK GL2 ET 1 -5°C +55°C K N CH 9 16321 KASK ET 1-M -5°C +55°C 3 CH 9

ANSI MARKINGS

CODE	COLOR	MARKING
WVI00040-500	CLEAR	ANSI Z87 + U6 X D3
WVI00040-510	SMOKE	ANSI Z87 + U6 L1.5 X D3
WVI00040-520	SILVER MIRROR	ANSI Z87 + U6 L2 X D3

ADDITIONAL INFORMATION

GUARANTEE
3 years starting from the date of purchase.

LIFE SPAN
10 years starting from the date of manufacture. Life span depends on various factors that can cause deterioration such as sudden temperature changes, the amount of exposure to direct sunlight and the intensity of use. Altered vision and scratches are elements that signal the need to check for deterioration of the visor.

CLEANING
Clean only with water and mild soap. Allow to air dry. Do not use chemical detergents, solvents, petrol powders as they are too aggressive and could lower the structural resistance of the visor.

3
YEARS
GUARANTEE

10
YEARS
LIFE SPAN

SCAN FOR COMPLETE COLLECTION

