



X1000

RESISTANCE & COMFORT

The X1000, our iconic ballistic goggles, are designed to meet all your needs. Its interchangeable CSP lenses options, each featuring our exclusive PLATINUM anti-fog and anti-scratch coating, are suited for various tactical scenarios. Compatible with all military equipments, it guarantees comfort, stability, and reliable protection, even during extended missions. With a matte black vented or sealed frame, the goggles are available as a military kit or a single unit system. The X1000 is the optimal choice for operators seeking maximum performance in extreme situations or challenging environments.

SUPPLIED WITH : KIT (Box, case, microfiber pouch, user instruction)

106 G

+ **CRYSTAL-CLEAR VISION WITH PLATINUM: ANTI-SCRATCH & ANTI-FOG COATING**

+ **HIGH-IMPACT BALLISTIC PROTECTION: MIL & STANAG**

+ **QUICK AND EASY LENS REPLACEMENT**

+ **PIVOT FOR HELMET WEARERS - QUICK RELEASE SYSTEM**



TECHNOLOGIES

CSP
PLATINUM

VERSIONS



X1000T10M



X1000T70M



X1000T00M



X1000T01M



X1000T02M



X1000T03M

NON-CONTRACTUAL PICTURES





X1000

REFERENCE	VERSION	LENS MARKING	FRAME MARKING	BALLISTIC RESISTANCE V50 STANAG 2920	MCEPS	COATING
X1000T10M	CLEAR	UL1.2 DT 1 KN C€	16321 UL1.2 GL2 DT 1-M 3 6 C€	867,6KM/H - 241M/S	GL-PD-10-12	PLATINUM
X1000T70M	CLEAR AMBER SMOKE	CLEAR: UL1.2 DT 1 KN C€ SMOKE: GL2 DT 1 KN C€ AMBER: UL1.2 DT 1 KN C€	16321 UL1.2 GL2 DT 1-M 3 6 C€	CLEAR: 867,6KM/H - 241M/S SMOKE: 871,9KM/H - 242,2M/S AMBER: 879,1KM/H - 244,2M/S	GL-PD-10-12	PLATINUM
X1000T00M	CLEAR	UL1.2 DT 1 KN C€		867,6KM/H - 241M/S	GL-PD-10-12	PLATINUM
X1000T01M	AMBER	UL1.2 DT 1 KN C€		879,1KM/H - 244,2M/S	GL-PD-10-12	PLATINUM
X1000T02M	SMOKE	GL2 DT 1 KN C€		871,9KM/H - 242,2M/S	GL-PD-10-12	PLATINUM

BOLLÉ SAFETY PRODUCT APPROVAL CERTIFICATES TO C€ STANDARDS WILL BE SENT ON REQUEST.

SPARE LENSES

PACKAGING & EAN13 CODE

SINGLE:	INNER BOX: Size: 24.3 x 18.3 x 9 cm Weight: 0.45 kg	OUTER PACK: Size: 58 x 38 x 30 cm Weight: 8.9 kg
		3660740220273 - 36 pcs
		3660740220266 - 22 pcs
	3660740120283 - 15 pcs	3660740220280 - 120 pcs
	3660740120290 - 15 pcs	3660740220297 - 120 pcs
	3660740120306 - 15 pcs	3660740220303 - 120 pcs
CUSTOM CODE: 9004901000		

BALLISTIC STANDARDS

STANAG 2920

MCEPS GL-PD-10-12


OPTIONAL ACCESSORIES

REFERENCE	DESCRIPTION	SINGLE:	INNER BOX:	OUTER PACK:
X1000T03M	RX INSERT - PC CLEAR	3660740020316	3660740120313	3660740220310

GENERAL SPECIFICATIONS

LENS	POLYCARBONATE - 3MM - CURVE 5	CE	EN166 - EN170
FRAME	TPV - SANTOPRENE - VENTED - INDIRECT VENTILATION - BREATHABLE FOAM	ANSI	ANSI Z87.1-2020
STRAP	NYLON POLYESTER - 35MM	AS/NZS	

KNOW MORE
ABOUT
MARKINGS:



OR SCAN:

CLEANING & STORAGE

CLEANING: The lenses should be cleaned regularly. Bolle Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.



MADE IN: TW

DATASHEET: 12-16-2024

bolle-safety.com

Europe Headquarters
34 rue de la Soie
69100 Villeurbanne
France
Tél. : 00 33 (0) 4 78 85 23 64

U.K. & Ireland
Unit C83 - Barwell Business Park
Leatherhead Road - Chessington
Surrey - KT9 2NY - UK
Tél. : 00 44 (0)208 391 4700

USA Office
2810 Caribou Court, Suite 160
Carlsbad, CA 92010
United States of America
Tél. : 800 222 6553

Asia-Pacific Office
32-40 Fairchild Street
heatherton VIC 3202
Australia
Tél. : 1300 138 098

